




BRAND-NEW
DESIGN



0.08S
LOW LATENCY



MULTIPLE FAN
MODES



DIRECT VIDEO
FOR LIVE STREAM



OPTIMIZED
MONITORING FEED



MULTIPLE
POWER OPTIONS



CHANNEL SCAN
FIRMWARE UPDATE ON APP


PARAMETERS

	Transmitter	Receiver
Interfaces	HDMI Input(Type A Female) SDI Input 2* Antenna Interfaces (RP-SMA Male) DC Input USB Type-C	HDMI Input(Type A Female) SDI Input 2* Antenna Interfaces (RP-SMA Male) DC Input USB Type-C
Supply Interfaces	DC Power Input:6-16V USB Type-C Power Supply:5V/2A Battery Power Supply:6-16V DC	DC Power Input:6-16V USB Type-C Power Supply:5V/2A Battery Power Supply:6-16V DC
Power Consumption	<11W	<7W
Weight	206g	206g
Dimension	(L*W*H): 110*72*33.5mm (The Battery Plate Exclude)	(L*W*H): 110*72*33.5mm (The Battery Plate Exclude)
Input / Output Video Format	HDMI:480p60 576p50 720p50/59.94/60 1080i50/59.94/60 1080p23.98/24/25/29.97/30 1080p50/59.94/60 SDI:1080p60/59.94/50(Level A) 1080p60/59.94/50(Level B) 1080i60/59.94/50 1080p30/29.97/25/24/23.98 1080P sF 25 720p60/59.94/50 1080P sF 24/23.98	HDMI:480p60 576p50 720p50/60 1080i50/60 1080p24/25/30 1080p50/60 SDI:1080p60/50(Level A) 1080p60/50 1080p30/25/24 720p60/50 1080i50(1080P sF 25/24/23.98input) 1080i60(1080P sF 30/29.97input)
Frequency	5GHz	5GHz
Modulation Mode	OFDM	OFDM
Transmission Power	Maximum 21dBm	/
Receiver Sensitive	/	80dBm
Transmission Latency	0.08s	0.08s
Bandwidth	20MHz	20MHz


PACKING LIST



Transmitter x1



Receiver x1



Antenna x5



DC Adapter x1



User Guide x1

*Please subject to actual shipment as the standard if any difference in accessories.