

*Run time in Minutes

Litepanels Lightning Range

Anton/Bauer Battery Type

On-Camera	Part Number	Wattage draw (W)	Amp draw (@13V)	Voltage range (VDC)	NP-F774 30 Watt/hr	NP-F976 47 Watt/hr	Dionic HC /Digital/Cine 90 Watt/hr	Hytron 100 100 Watt/hr	Digital 150/Cine 150 150 Watt/hr	Digital 190 190Watt/hr	Hytron 140 140Watt/hr
Croma 2	MLCROMA2	14	2.2-0.8	6.5-18	125 ⁻¹	200 ⁻¹	385 ⁻²	425 ⁻³	640 ⁻²	810 ⁻²	600 ⁻³
MicroPro 2	MLMICROPRO2	14	2.2-0.8	6.5-18	125 ⁻¹	200 ⁻¹	385 ⁻²	425 ⁻³	640 ⁻²	810 ⁻²	600 ⁻³
Spectra 2	MLSPECTRA2	8	1.2-2.3	6.5-18	225 ⁻⁴	350 ⁻⁴	675 ⁻²	750 ⁻³	1,125 ⁻²	1,425 ⁻²	1,050 ⁻³
Brick Bi-Color	915-1003	18	1.5-1.1	12-17	•	•	300	330	500	630	465

*1 Include L-Series Battery Plate (MLBATTADT-L7.2V) *2 D-Tap* Power Cable (900-6104) *3QRC-LG Gold Mount* Stand Mount (8375-0176) with D-Tap* Power Cable (900-6104) *4 L-Series Battery Plate (MLBATTADT-L7.2V)

LED Panels

LED Panels	Part Number	Wattage draw (W)	Amp draw (@13V)	Voltage range (VDC)	NP-F774 30 Watt/hr	NP-F976 47 Watt/hr	Dionic HC /Digital/Cine 90 90 Watt/hr	Hytron 100 100Watt/hr	Digital 150/Cine 150 150 Watt/hr	Digital 190 190 Watt/hr	Hytron 140 140Watt/hr	VCLX 560 Watt/hr	VCLX/2 280 Watt/hr	
Lykos Daylight	MLL1500-D	23	3.5-13	6.5-18	75 ⁻¹	120 ⁻¹	120 ⁻¹	260 ⁻³	425 ⁻³	640 ⁻²	365 ⁻²	•	•	
Lykos Bi-Color	MLL1300-BI	23	3.5-1.3	6.5-18	75 ⁻¹	120 ⁻¹	120 ⁻¹	260 ⁻³	425 ⁻³	640 ⁻²	365 ⁻²	•	•	
ASTRA														
Astra 3x Daylight	935-2021	55	4.1-1.65	12.5-31	•	•	98 ⁻⁴	109 ⁻⁴	164 ⁻⁴	207 ⁻⁴	153 ⁻⁴	611 ⁻⁵	305 ⁻⁵	
Astra 3x Bi-Color	935-2023	55	4.1-1.65	12.5-31	•	•	98 ⁻⁴	109 ⁻⁴	164 ⁻⁴	207 ⁻⁴	153 ⁻⁴	611 ⁻⁵	305 ⁻⁵	
Astra 6x Daylight	935-1021	105	8.5-3.42	12.5-31	•	•	51 ⁻⁴	57 ⁻⁴	86 ⁻⁴	109 ⁻⁴	80 ⁻⁴	320 ⁻⁵	160 ⁻⁵	
Astra 6x Bi-Color	935-1023	105	8.5-3.42	12.5-31	•	•	51 ⁻⁴	57 ⁻⁴	86 ⁻⁴	109 ⁻⁴	80 ⁻⁴	320 ⁻⁵	160 ⁻⁵	
Astra Soft Bi-Color	935-5021	105	8.5-3.42	12.5-31	•	•	51 ⁻⁴	57 ⁻⁴	86 ⁻⁴	109 ⁻⁴	80 ⁻⁴	320 ⁻⁵	160 ⁻⁵	
HILIO														
Hilio D12 Daylight	907-2001	310	7.6-5.2	41-60	No Anton/Bauer Mobile Power Solution Available									
Hilio D12 Daylight	907-2003	310	7.6-5.2	41-60	No Anton/Bauer Mobile Power Solution Available									
GEMINI														
Gemini		325	11.6	28	•	•	n/a	n/a	n/a	n/a	n/a	n/a	n/a	

*1 Include L-Series Battery Plate (MLBATTADT-L7.2V) *2 D-Tap* Power Cable (900-6104) *3QRC-LG Gold Mount* Stand Mount (8375-0176) with D-Tap* Power Cable (900-6104) *4 Astra Gold Mount* Battery Plate with P-Tap to 3-Pin XLR Cable (900-3507) or Astra V-Mount Battery Plate with P-Tap to 3-Pin Cable (900-3508) (VCLX) *5 Included 3-Pin XLR Power Cable (VCLX) *6 (2) 14.4V battery plate (Gold Mount and V-Mou options Coming Soon)

LED Fresnel

LED Fresnel	Part Number	Wattage draw (W)	Amp draw (@13V)	Voltage range (VDC)	Dionic HC/Digital/Cine 90 90 Watt/hr	Hytron 100 100 Watt/hr	Digital 150/Cine 150 150 Watt/hr	Digital 190 190 Watt/hr	Hytron 140 140Watt/hr	VCLX 560Watt/hr	VCLX/2 280 Watt/hr	
HILIO												
Inca 4	906-4003	36	3.10-1.18	11.6-30.4	150 ⁻¹	165 ⁻¹	250 ⁻¹	315 ⁻¹	230 ⁻¹	930 ⁻²	460 ⁻²	
Inca 6	906-2003	95	8.19-2.98	11.6-31.9	55 ⁻³	60 ⁻³	90 ⁻³	120 ⁻³	85 ⁻³	930 ⁻²	460 ⁻²	
Inca 9	906-5003	172	4.3-2.9	40-60	No Anton/Bauer Mobile Power Solution Available							
Inca 12	906-2003	320	8.0-5.33	40-60	No Anton/Bauer Mobile Power Solution Available							
SOLA / Daylight												
Caliber	909-1001	13.1	2.38-1.01	5.5-13	415 ⁻⁶	460 ⁻⁶	690 ⁻⁶	875 ⁻⁶	645 ⁻⁶	•	•	
Sola ENG	906-1002	27	2.7-1.35	10-20	200 ⁻⁵	220 ⁻⁶	330 ⁻⁵	875 ⁻⁶	645 ⁻⁶	•	•	
Sola 4+	906-4024	53	3.10-1.18	11.6-30.4	102 ⁻¹	113 ⁻¹	170 ⁻¹	215 ⁻¹	158 ⁻¹	634 ⁻²	317 ⁻²	
Sola 6+	906-2024	104	8.19-2.98	11.6-31.9	52 ⁻³	58 ⁻³	87 ⁻³	110 ⁻³	81 ⁻³	323 ⁻⁴	162 ⁻⁴	
Sola 9	906-5001	172	4.3-2.9	40-60	No Anton/Bauer Mobile Power Solution Available							
Sola 12	906-3001	320	8.0-5.33	40-60	No Anton/Bauer Mobile Power Solution Available							

1 QRC-LG Gold Mount Stand Mount (8375-0176) PowerTap 36 XLR 4-Pin (8075-0135) with 7ft PowerTap Ext (8075-0010) *2 Included 4-Pin XLR Power Cable *3 QRC-LG Gold Mount* Stand Mount (8375-0176) 3-Pin XLR to 2-Pin D-Tap* Power Cable (900-0024) and 7ft PowerTap Ext (8075-0010) *4 Included 3-Pin XLR Power Cable *5 Included D-Tap* Cable *6 3rd party D-Tap* Cable *4 Astra Gold Mount* Battery Plate with P-Tap to 3-Pin XLR Cable (900-3507) or Astra V-Mount Battery Plate with P-Tap to 3-Pin Cable (900-3508) (VCLX)

For more product information visit: Litepanels.com | Antonbauer.com

Results are based on fully charged brand new batteries. Information published on 17 November 2016. Specifications are subject to change without notice