

SWIT®

Bi-color SMD-LED On-camera Light

- Surface mounted LED
- Wider beam angle
- 3200K~5600K adjust
- Super high CRI & TLCI



S-2240
60 SMD-LEDs



S-2241
153 SMD-LEDs

12W power, 300Lux @ 1 meter center
120°(half-declined 68°) wide beam angle
3200K-5600K continuously adjustable
10%-100% flick-free dimming
Super high CRI Ra ≥ 92, TLCI ≥ 97
143(W)×91(H)×34(D)mm, 166g

20W power, 640Lux @ 1 meter center
120°(half-declined 68°) wide beam angle
3200K-5600K continuously adjustable
10%-100% flick-free dimming
Super high CRI Ra ≥ 92, TLCI ≥ 97
143(W)×91(H)×34(D)mm, 182g

Magnetic installed diffuser cover



Diffuser of PC material with organic light diffusion agent, which increased the transmission of light, and provides a soft, glareless and comfortable lighting effect

Quick Release and Interchangeable DV battery plates



"Snap-on type Battery Plates"

S-7004F
S-7004U
S-7004D
S-7004B
S-7004V
S-7004i
S-7004C
S-7004E

Compatible batteries

SONY NP-F970/770,	SWIT S-8972, S-8970
SONY BP-U60/U30	SWIT S-8U93, S-8U63
Panasonic CGA-D54, VW-VBD58	SWIT S-8D98, S-8D58, S-8D62
Panasonic VW-VBG6	SWIT S-8BG6
JVC BN-VF823	SWIT S-8823
SSL-JVC50	SWIT S-8i50, S-8i75
Canon BP-945/970G	SWIT S-8845, S-8945
Canon LP-E6	SWIT S-8PE6

Standard Accessories:



Portable Bag x1

Magnetic Diffuser Cover x1

D-tap cable

S-7004 series
Snap-on plate x1

Cold shoe / Screw
Ball head x1