

AG-CX10 Specifications

SENSOR SECTION	
Image Sensor	1/2.5-type (inch) MOS Sensor
Effective Pixels	8.29 megapixels
LENS SECTION	
F Value	F1.8-4.0
Optical Zoom	24x
Focal Length	4.12-98.9mm
35 mm Film Camera Equivalent	25.0-600.0 mm
Filter Diameter	62 mm
Lens Brand	Leica Dicomar Lens
CAMERA SECTION	
Minimum Illumination	1.5 lx (F1.8, Super Gain +, 1/30)
Focus	Auto / Manual
Zoom	Intelligent Zoom OFF: 24x
	Intelligent Zoom ON: Max. 48x (UHD 32x)
	Digital Zoom: 2x / 5x / 10x
ND Filter	1/4, 1/16, 1/64, OFF
IR Filter	Incorporates the ON/OFF control function
White Balance	Auto / ATW LOCK / 3200K / 5600K / VAR (2000K-15000K) / Ach Fixed / Bch Fixed
Shutter Speed	59.94 Hz mode ·59.94i/59.94p: 1/60, 1/100, 1/120, 1/180, 1/250, 1/350, 1/500, 1/750, 1/1000, 1/1500, 1/2000, 1/3000, 1/4000, 1/8000 sec ·29.97p: 1/30, 1/50, 1/60, 1/100, 1/120, 1/180, 1/250, 1/350, 1/500, 1/750, 1/1000, 1/1500, 1/2000, 1/3000, 1/4000, 1/8000 sec ·23.98p: 1/24, 1/48, 1/50, 1/60, 1/100, 1/120, 1/180, 1/250, 1/350, 1/500, 1/750, 1/1000, 1/1500, 1/2000, 1/3000, 1/4000, 1/8000 sec
	50.00 Hz mode ·50i/50p: 1/50, 1/60, 1/100, 1/125, 1/180, 1/250, 1/350, 1/500, 1/750, 1/1000, 1/1500, 1/2000, 1/3000, 1/4000, 1/8000 sec ·25p: 1/25, 1/50, 1/60, 1/100, 1/125, 1/180, 1/250, 1/350, 1/500, 1/750, 1/1000, 1/1500, 1/2000, 1/3000, 1/4000, 1/8000 sec
Slow Shutter Speed	59.94 Hz mode 59.94i/59.94p: 1/8, 1/15, 1/30 sec 29.97p: 1/8, 1/15 sec 23.98p: 1/6, 1/12 sec
	50.00 Hz mode 50i/50p: 1/6, 1/12, 1/25 sec 25p: 1/6, 1/12 sec
Super Slow Recording Frame Rate	59.94 Hz mode FHD 120 fps (1/2 speed at 60p, 1/4 speed at 30p, 1/5 speed at 24p)
	50.00 Hz mode FHD 100 fps (1/2 speed at 50p, 1/4 speed at 25p)
Iris	Auto / Manual
Image Stabilizer	Ball O.I.S., 5-Axis HYBRID O.I.S. (UHD/FHD)
RECORDING SECTION	
Recording Media	SDHC/SDXC Memory Card, microP2 card (A series, B series)
Recording Format	MOV, MP4, AVCHD, P2
Video Compression Method	MOV/MP4: H.264/MPEG-4 AVC High Profile, H.265/MPEG-H HEVC Main10 Profile AVCHD: H.264/MPEG-4 AVC High Profile P2: AVC-LongG 50/AVC-LongG25: MPEG-4 AVC/H.264 High Profile

Audio Compression Method	MOV / P2: LPCM (24bit 2ch) MP4: AAC (16bit 2ch) AVCHD: Dolby Audio (16bit 2ch)
System Frequency	59.94Hz / 50.00Hz
Recording / Playback Mode	MOV (HEVC) [4:2:0 10bit] UHD 3840 x 2160 59.94p/50.00p HEVC 200M: Average 200 Mbps (VBR) UHD 3840 x 2160 29.97p/25.00p/23.98p HEVC 150M: Average 150 Mbps (VBR)
	MOV [4:2:0 8bit] UHD 3840 x 2160 59.94p/50.00p 150M: Average 150 Mbps (VBR) UHD 3840 x 2160 29.97p/25.00p/23.98p 100M: Average 100 Mbps (VBR) [4:2:2 10bit] UHD 3840 x 2160 29.97p/25.00p/23.98p 150M: Average 150 Mbps (VBR) FHD 1920 x 1080 59.94p/50.00p 200M (ALL-Intra): Average 200 Mbps (VBR) FHD 1920 x 1080 29.97p/25.00p/23.98p 100M (ALL-Intra): Average 100 Mbps (VBR) FHD 1920 x 1080 59.94i/50i 100M (ALL-Intra): Average 100 Mbps (VBR) FHD 1920 x 1080 59.94p/50.00p 100M: Average 100 Mbps (VBR) FHD 1920 x 1080 29.97p/25.00p/23.98p/59.94i/50.00i 50M: Average 50 Mbps (VBR)
	MP4 (HEVC) [4:2:0 10bit] UHD 3840 x 2160 59.94p/50.00p HEVC 100M: Average 100 Mbps (VBR) UHD 3840 x 2160 29.97p/25.00p/23.98p HEVC 72M: Average 72 Mbps (VBR)
	MP4 [4:2:0 8bit] UHD 3840 x 2160 29.97p/25.00p/23.98p 72M: Average 72 Mbps (VBR) FHD 1920 x 1080 59.94p/50.00p/23.98p 50M: Average 50 Mbps (VBR)
	AVCHD [4:2:0 8bit] PS 1920 x 1080 59.94p/50.00p: Average 25 Mbps (VBR) PH 1920 x 1080 59.94i/50.00i/23.98p: Average 21 Mbps (VBR) HA 1920 x 1080 59.94i/50.00i: Average 17 Mbps (VBR) PM 1280 x 720 59.94p/50.00p: Average 8 Mbps (VBR)
	P2 [4:2:2 10bit] FHD 1920 x 1080 59.94p/50.00p/59.94i/50.00i: Average 50 Mbps (VBR) FHD 1920 x 1080 59.94i/50i: Average 25 Mbps (VBR) HD 1280 x 720 59.94p/50.00p: Average 50 Mbps (VBR) HD 1280 x 720 59.94p/50.00p: Average 25 Mbps (VBR)
LIVE STREAMING	
Video Compression Format	H.264/MPEG-4 AVC Main Profile, High Profile
Video Resolution	1920 x 1080 (FHD), 1280 x 720 (HD), 640 x 360, 320 x 180
Streaming Method	Unicast, Multicast
Frame Rate	System frequency = 59.94 Hz: 30 fps, 60 fps System frequency = 50.00 Hz: 25 fps, 50 fps
Bit Rate	24 Mbps, 20 Mbps, 16 Mbps, 14 Mbps, 8 Mbps, 6 Mbps, 4 Mbps, 3 Mbps, 2 Mbps, 1.5 Mbps, 1 Mbps, 0.7 Mbps, 0.5 Mbps
Audio Compression Format	AAC-LC, 48 kHz/16 bit, 2ch
Network Protocol	RTSP/RTP/RTMP/RTMPS
STILL IMAGE SECTION	
Recording Format	JPEG (DCF/Exif2.2)
Recording Image Size*	Video Playback Mode: 3840 x 2160 (16:9), 1920 x 1080 (16:9), 1280 x 720 (16:9)
GENERAL SECTION	
Power Supply	7.28V (Battery) / 12V (AC Adaptor)
Power Consumption	15.5W (LCD Monitor)
Dimensions (W x H x D)	Approx. 129 x 159 x 257 mm (5.08 x 6.26 x 10.1 inch)
Weight	Body: approx. 0.9kg (1.98 lb) (body only, excluding handle, lens hood, battery, and accessories) Shooting: approx. 1.5kg (3.31 lb) (including handle, lens hood, battery, and eyecup)
LCD Monitor	8.88 cm (3.5-inch) Wide LCD monitor (About 2,760,000 dots) (For Europe) 3.5-inch Wide LCD monitor (About 2,760,000 dots) (For North America / Asia)
Viewfinder	0.61 cm (0.24-inch) Wide EVF (About 1,560,000 dots) (For Europe) 0.24-inch Wide EVF (About 1,560,000 dots) (For North America / Asia)
Manual Ring	Focus / Zoom or Iris

Accessory Shoe	Yes
LED Video Light	Average Illumination: Approx. 70 lx (1.0m)
	Irradiation Angle: Approx. 30°
	Color Temperature: Approx. 4600K
INTERFACE SECTION	
Video	SDI OUT: BNC x 1, 0.8V[p-p], 75Ω, 3G/1.5G HD-SDI supported Output format: 1080/59.94p LEVEL-A/50.00p LEVEL-A, 1080/29.97PsF/25.00PsF/23.98PsF, 1080/59.94i/50.00i, 720/59.94p/50.00p
	HDMI: Type A x 1 (VIERA Link not supported) Output format: 2160/59.94p/50.00p/29.97p/25.00p/23.98p, 1080/59.94p/50.00p/29.97p/25.00p/23.98p/59.94i/50.00i, 720/59.94p/50.00p, 480/59.94p, 576/50.00p
Audio Input	Built-in Microphone: Stereo microphone
	Microphone Input: 3.5mm stereo mini jack x 1 XLR Input: XLR (3 pins) x 2 Input high impedance, LINE/MIC/MIC+48 V (switchable SW) LINE: +4dBu/0dBu (switchable menu) MIC: -40dBu/-50dBu/-60dBu (switchable menu)
Audio Output	SDI: 2 ch (LPCM 24bit) Gain: 0dB/-6dB/-8dB
	HDMI: 2 ch (LPCM 24bit)
	Headphone: 3.5 mm diameter stereo mini jack x 1
	Speaker: 15 mm diameter, round x 1
Other Input/Output	Camera Remote: 2.5mm super mini jack x 1
	USB 2.0 HOST: Micro-AB connector, 5-pin, only USB LAN conversion supported
	USB 2.0 DEVICE: Micro-AB connector, 5-pin, mass storage function (read only)
	DC IN: DC 12V (11.4V - 12.6V) EIAJ Type4
Wi-Fi	
Standard	IEEE 802.11b/g/n
Frequency	2.4GHz band
STANDARD ACCESSORY	
AC Adaptor	Yes
AC Cable	Yes
Rechargeable Battery Pack	Yes (5,900mAh)
Handle Unit	Yes (detachable)
Battery Charger	-
IR Remote	-
HDMI Cable	-
AV Cable	-
USB Cable	Yes (Micro-AB to Host)
USB LAN Conversion Adaptor	Yes (VW-UEA1)
Microphone Holder	Yes
Microphone Holder Screws	Yes
Input Terminal Cap	-
Eye Cup	Yes
Lens Hood	Yes
Editing Software	-

* Only images cut from video in video playback mode are supported.
Note: Specifications are subject to change without notice.