



Scheduled for release in June 2019





Preliminary

1/2.3-type MOS 20x (optical zoom Digi		al Zoom/i.Zoom	DRS/DNR/HDR	OIS	PoE+	IP control	
HD image IP transmission		Up to 100 presets		Audio Input	USB Video Class	М	MicroSD Card Recording		

Integrated pan-tilt full-HD cameras supporting 3G-SDI output via HDMI, USBand IP transfer

- •1080/59.94p, 29.97p, 59.94i, 29.97PsF, 1080/50p, 25p, 50i, 25PsF, 720/59.94p and 50p video formats are supported.
- •Ultra-high resolution technology with optical 20x zoom ensures high resolution at up to 30x zoom.
- •Optical Image Stabilizer (OIS)/4-axis hybrid image stabilizer are equipped.
- Equipped with a four Drive Lens System where three zoom lenses and one focus lens independently operate simultaneously.
- •Blown-out highlights and blocked-up shadows can be corrected with High Dynamic Range (HDR) mode.
- •Night mode with automatic switching supports shooting in low-light locations.
- Equipped with a Freeze During Preset function that freezes video during preset playback.
- •Full-HD video output is supported via IP transfer in addition to HDMI, SDI and USB output.
- •Generator-lock function is equipped.
- •The IP control browser supports camera control from remote locations. PC, Mac and mobile devices are supported.
- Power supply via a LAN cable is supported with PoE+. This reduces wires used and cost.
- •External control of recording start/stop operations and transfer of saved files to an FTP server can be performed via an IP network.
- •The AW-HE42W/K can be upgraded to NDI I HX by purchasing a license*4.
- •Equipped with a JPEG Image Saving function that enables camera video to be saved, played back and deleted on a microSD card as still JPEG images.